

SEV 3500

Solar storage inverter

Efficiency

- Advanced MPPT with up to 99.9% efficiency
- Mivultiple charge and discharge modes are available

SAIL SOLAR

Safety

- 360 degrees of security from hardware to software
- Multiple safety approvals available

All in one

- Support for many types of batteries
- Supports Li-ion battery BMS communication

Reliable

- · Outputs high-quality pure sine wave AC power
- · Reliable output for long periods at rated power

User-Friendly

- Industrial design with a modern aesthetic look
- Easy to install and simple to use

Intelligent

- Exclusive Li-ion battery BMS dual activation
- Support for remote monitoring of operating

Application scenario















MODEL	SEV 3500	CAN BE SE
INVERTER		
Rated Output Power	3,500W	
Max.Peak Power	6,000VA	
Rated Output Voltage	230Vac (L/N/PE single phase)	~
Load Capacity of Motors	2HP	
Rated AC Frequency	50Hz/60Hz	~
Waveform	Pure Sine Wave	
Switch Time	10ms (typical)	
BATTERY		
Battery Type	Lead-acid / Li-ion / User defined	*
Rated Battery Voltage	24V	
Voltage Range	20 ~ 33Vdc	*
Max.MPPT Charging Current	80A	~
Max.Mains/Generator Charging Current	80A	~
Max.Hybrid Charging Current	80A	*
PV INPUT		
Num. of MPPT Trackers	1	
Max.PV Array Power	4,000W	
Max.Input Current	13A	
Max.Voltage of Open Circuit	500Vdc	
MPPT Voltage Range	120-450Vdc	
UTILITY/ GENERATOR INPUT		
Input Voltage Range	UPS mode: 170 ~ 280Vac; APL mode: 90 ~ 280Vac	*
Frequency Range	50/60Hz	
Bypass Overload Current	30A	
EFFICIENCY		
MPPT Tracking Efficiency	99.9%	
Max. Battery Inverter Efficiency	92%	
GENERAL		
Dimensions	378*280*103mm (1.24*0.92*0.34ft)	
Weight	7.4kg (16.31lb)	
Protection Degree	IP20, Indor Only	
Operating Temperature Range	-10°C~55°C	
Noise	≤60dB	
Cooling Method	Internal Fan	
Warranty	1.5 Years	
COMMUNICATION		
Embedded Interfaces	RS485 / CAN / USB / Dry contact	/
External Modules (Optional)	Wi-Fi / GPRS	· /
CERTIFICATION		· ·
Safety	CE(IEC 62109-1)/FCC/SAA	
EMC	EN61000, C2	
RoHS	Yes	

